peaks are used to estimate the time offsets of the corresponding signals, giving sufficient independent timing measurements (three in this case) to compute a position fix.

5   If the peak 601 corresponding to the signals from Node B 203 is too weak to be resolved, a further iteration could be undertaken in which the signals from Node B 202 could be subtracted to yield a second residual signal (Figure 7). There is a clear correlation peak 701 at a delay of approximately 7 chips as expected.

10   In the prior art method of EP 01306115.5 discussed above, the assumption is made that the signal received at the terminal is a simple sum of the transmitted signals attenuated, phase rotated and delayed by the individual path lengths between transmitter and receiver. In a more complex system in which the transmission channel has incorporated non-linear effects, multi-path and noise, the transmitted signal is

15   further degraded by these effects making the edges of the waveform less clearly defined in time. This process we have called a 'blurring' of the signal. When attempting to cancel a blurred signal, the process of subtracting only a simply scaled, delayed and phase rotated copy of the signal recorded by one sampling device from the signal received at the terminal may not remove the contribution from the

20   transmitter associated with the one sampling device accurately enough. The present invention therefore provides improved methods which remove more accurately the contribution of the signals from the transmitter associated with the one sampling device from the signals received at the terminal by creating an equivalently 'blurred' estimate of the signal recorded at the terminal.

25

This process requires the creation of short sections of the recorded and sampled baseband representations of the signal to be used in the method. We have called such a section of data 'a section of the representation of the signal' in the following description.

30

A first aspect of the invention therefore provides a method of finding the time offset between signals transmitted by at least one of a plurality of transmitters of a communications network and received by a receiver attached to a terminal, the method comprising the steps of

35   (a) creating at the terminal a section of a representation of the signals from the transmitters received by the receiver;

REPLACED BY

8   ART 34 AMDT

(b) creating a first section of a representation of the signal transmitted by a first of said transmitters, and creating a second section of a representation of the signal transmitted by a second of said transmitters, each of which sections overlaps in time with the section created at the terminal;

5   (c) calculating a blurred estimate of the signal received at the terminal from the first transmitter using a first function dependent on the first section and the section created at the terminal in step (a);

(d) creating a blurred terminal section using a second function dependent on the first section and the section created at the terminal in step (a);

10   (e) subtracting the blurred estimate from the blurred terminal section to produce a blurred residual representation; and

(f) estimating the time offset between the blurred residual representation and the second section.

15   Preferably, the first function, which is used to create the blurred estimate, is a convolution of the first section of a representation of the signal transmitted by a first of said transmitters (the 'first section') with a cross-correlation of the section of a representation of the signals from the transmitters received by the receiver (the 'terminal section') and the first section.   The above cross-correlation is preferably a

20   windowed cross-correlation created by enhancing the significant components of the cross-correlation function.

Similarly, the second function, which is used to create the blurred terminal section, is a convolution of the terminal section with the auto-correlation profile of the first

25   section.

Preferably, the blurred residual representation is cross-correlated with the second section of a representation of the signal transmitted by a second of said transmitters (the 'second section') to estimate the time offset.

30

Preferably, the first and second sections are created at the respective first and second transmitters, but they may be created elsewhere. They may be created in one or more sampling devices attached to the respective transmitters or located elsewhere, or they may be created by computer programs running anywhere in the

35   communications network, or elsewhere, using information supplied from the network about the transmitted signals.

The various signal representation sections may be sent to one or more computing devices in which said estimates and time offsets, and a terminal location estimate, may be calculated. In some embodiments, the time offset between said section of a representation of the signals received by the receiver and said first section may first be calculated, and may then be used in the calculation of said terminal location estimate. The time offset between said section of a representation of the signals received by the receiver and said first section may be calculated using said sections or it may be calculated by other means, for example by calculating the time offset of a known component of the signal such as a pilot code. The time offset between said blurred residual representation and said second section may be calculated using said second section or it may be calculated by other means, for example by using a known component of the signal such as a pilot code.

The present invention thus overcomes the hearability problem by, for example, using a separate sampling device for each transmitter which sends to a computing device a representation of the signals transmitted only by that transmitter, by performing a cross-correlation of the representation sent back by the mobile terminal with the representation sent back by the sampling device associated with one of the transmitters to estimate the time offset between them, and by subtracting a blurred estimate of that signal from a blurred representation sent back by the mobile terminal, in order to reduce its effect on the remaining signals as far as possible. The cross-correlation and blurred subtraction steps may be iterated until no useful signals remain to be extracted. Simulations show that this provides a greater hearability gain than the straight subtraction method of the prior art of EP 01306115.5 while maintaining the advantages over IP-DL.

In some systems, the hearability problem may be solved simply by subtracting a blurred estimate of the signals received from just one transmitter, usually the brightest, from a blurred representation of the signals received at the terminal leaving a blurred residual representation in which the time offsets of the pilot codes, blurred pilot codes or any other known portions of the transmitted signals, may be determined.

Thus a second aspect of the invention therefore provides a method of finding the time offset relative to a reference within the terminal of a component of a signal transmitted by one of a plurality of transmitters of a communications network and received by a receiver attached to a terminal, the method comprising the steps of

REPLACED BY
ART 34 AMDT

(a) creating at the terminal a section of a representation of the signals from the transmitters received by the receiver (a "terminal section");

(b) creating a section of a representation of the signal transmitted by an other transmitter (a "transmitter section"), which section overlaps in time with the
5   section created at the terminal;

(c) calculating a blurred estimate of the signal received at the terminal from the other transmitter using a first function dependent on the transmitter section and the terminal section;

(d) creating a blurred terminal section using a second function dependent on
10   the transmitter section and the terminal section;

(e) subtracting the blurred estimate from the blurred terminal section to produce a blurred residual representation; and

(f) estimating the time offset between the blurred residual representation and the signal component.

15

Preferably, the first function, which is used to create the blurred estimate, is a convolution of the transmitter section with a cross-correlation of the terminal section and the transmitter section.   This cross-correlation is preferably a windowed cross-correlation created by enhancing the significant components of the cross-correlation
20   function.

Similarly, the second function, which is used to create the blurred terminal section, is a convolution of the terminal section with the auto-correlation profile of the transmitter section.

25

The known components of the transmitted signals in the second aspect of the invention may, for example, be the pilot codes. Before the time offset is estimated the known signal components may be blurred by convolution with another function.

30   In both the first and the second aspects of the invention, the section of the representation of the signals received by the receiver at the terminal may be recorded in the terminal before being sent to a computing device. Alternatively, the section may be transferred in real time to the computing device and a recording made there.

35   Preferably, the section of the representation of the signals transmitted by a transmitter is created at that transmitter, but it may be created elsewhere. It may be created in a sampling device attached to the transmitter or located elsewhere, or it may be created

by a computer program running anywhere in the communications network, or elsewhere, using information supplied from the network about the transmitted signals. The calculations may be carried out in a computing device which may be in the handset or elsewhere, for example, a processor connected to the network.

5

The terminal may be a part of a positioning system, for example as described in any of EP-A-0767594, WO-A-9730360, AU-B-716647 EP-B-0303371, US-A-6094168 and EP-A-1025453 and may be a fixed device associated with a transmitter (for example, the 'fixed receiver' or 'Location Measurement Unit, LMU'), whose purpose is to

10 receive signals from distant transmitters as well as from its associated transmitter, in which case the method of the invention includes the estimation of and subtraction of the signals from its associated transmitter in order to allow it to measure the time offsets of the signals received from distant transmitters.

15 The representation of the signals received by the receiver attached to the terminal may be a digitised version of the received signals converted first to baseband in the receiver. The representation of the signals transmitted by a transmitter may be a digitised version of the transmitted signals converted first to baseband.

20 In order to ensure an overlap of the respective sections, a suitably chosen component of the transmitted signals may be used to indicate the start of sampling.

The invention also includes apparatus including a processing means arranged to carry out the method of the first or second aspects of the invention described above.

25

The apparatus for carrying out the first aspect of the invention may comprise

(a) processing means arranged to create at the terminal a section of a representation of the signals from the transmitters received by the receiver;

(b) processing means arranged to create a first section of a representation of

30 the signal transmitted by a first of said transmitters, and to create a second section of a representation of the signal transmitted by a second of said transmitters, each of which sections overlaps in time with the section created at the terminal;

(c) processing means arranged to calculate a blurred estimate of the signal received at the terminal from the first transmitter using a first function dependent on

35 the first section and the section created at the terminal in step (a);

REPLACED BY
ART 34 AMDT

(d) processing means arranged to create a blurred terminal section using a second function dependent on the first section and the section created at the terminal in step (a);

(e) processing means arranged to subtract the blurred estimate from the blurred terminal section to produce a blurred residual representation; and

(f) processing means arranged to estimate the time offset between the blurred residual representation and the second section.

The apparatus for carrying out the second aspect of the invention, for finding the time offset relative to a reference within the terminal of a component of a signal transmitted by one of a plurality of transmitters of a communications network and received by a receiver attached to a terminal, may comprise

(a) processing means arranged to create at the terminal a section of a representation of the signals from the transmitters received by the receiver (a "terminal section");

(b) processing means arranged to create a section of a representation of the signal transmitted by an other transmitter (a "transmitter section");

(c) processing means arranged to calculate a blurred estimate of the signal received at the terminal from the other transmitter using a first function dependent on the transmitter section and the terminal section;

(d) processing means arranged to create a blurred terminal section using a second function dependent on the transmitter section and the terminal section;

(e) processing means arranged to subtract the blurred estimate from the blurred terminal section to produce a blurred residual representation; and

(f) processing means arranged to estimate the time offset between the blurred residual representation and the signal component.

The apparatus may be disposed in a handset or other terminal of a telecommunications network.

The invention also includes a communications network for carrying out the first aspect of the invention, the network comprising

(a) a computing device or devices;

(b) a terminal having a radio receiver attached to the terminal, means for creating a section of a representation of the signals, received by the radio receiver, from the transmitters of the communications network, and means for sending the section to the computing device or devices;

(c) sampling devices associated with respective first and second of said transmitters for creating respective first and second sections of representations of the signal transmitted by the respective transmitter which overlap in time with the section created at the terminal, and for sending the

5   sections of the representations created at said transmitters to said computing device or devices;

the computing device or devices being adapted to perform

1   a calculation of a blurred estimate of the signal received at the terminal from the first transmitter using a first function dependent on the first section and the

10   section created at the terminal;

2   a calculation of a blurred terminal section using a second function dependent on the first section and the section created at the terminal;

3   a subtraction of said blurred estimate from the blurred terminal section to produce a blurred residual representation;

15   4   a calculation of the time offset between the blurred residual representation and said second section.

A calculation of the position of the terminal may be made using said time offset.

20   The invention also includes a communications network for carrying out the second aspect of the invention, for finding the time offset relative to a reference within the terminal of a component of a signal transmitted by one of a plurality of transmitters of a communications network and received by a receiver attached to a terminal, the network comprising

25   (a) a computing device or devices;

(b) a terminal having a radio receiver attached to the terminal, means for creating a section of a representation of the signals, received by the radio receiver, from the transmitters of the communications network (a "terminal section"), and means for sending the section to the computing device or devices;

30   (c) a sampling device associated with an other transmitter for creating a section of a representation of the signal transmitted by the other transmitter (a "transmitter section") which overlaps in time with the section created at the terminal, and for sending the section of the representations created at the other transmitter to said computing device or devices;

35   the computing device or devices being adapted to perform

14

1   a calculation of a blurred estimate of the signal received at the terminal from the other transmitter using a first function dependent on the transmitter section and the terminal section;

2   a calculation of a blurred terminal section using a second function dependent on the transmitter section and the terminal section;

3   a subtraction of said blurred estimate from the blurred terminal section to produce a blurred residual representation;

4   a calculation of the time offset between the blurred residual representation and the signal component.

A calculation of the position of the terminal may be made using said time offset.

The E-OTD positioning systems described generally above work with unsynchronised networks, i.e. any common component of the signals transmitted by any one transmitter is not synchronised in time with the transmission of that component by any other of the transmitters, but instead is transmitted after an unknown time delay, sometimes called the Relative Transmission Delay (RTD). The position calculation requires that this delay is known, and so the positioning systems employ fixed receivers at known locations throughout the network which are set up to measure the transmitted signals and compute the RTDs. It has been described above how the hearability problem hinders the straightforward application of the E-OTD techniques to direct-sequence CDMA systems. However, the second aspect of the present invention overcomes the hearability problem by allowing the very strong signals from a local transmitter to be subtracted from the signals received by the fixed receiver, thus allowing the much weaker signals from the distant transmitters to be measured. The method of application of E-OTD to CDMA systems then follows that described, for example, in our EP-A-1025453.

The invention also includes one or more computing devices in which the calculations described herein above are made.

The means for carrying out the calculations in the computing device or devices may be components of hardware and/or software.

Therefore, the invention includes a computer program or programs having computer program code means for carrying out the steps performed in the computing device or devices as described above.

CLAIMS

1.   A method of finding the time offset between signals transmitted by at least one
of a plurality of transmitters of a communications network and received by a receiver
5   attached to a terminal, the method comprising the steps of

        (a) creating at the terminal a section of a representation of the signals from the
        transmitters received by the receiver;

        (b) creating a first section of a representation of the signal transmitted by a
        first of said transmitters, and creating a second section of a representation of
10   the signal transmitted by a second of said transmitters, each of which sections
        overlaps in time with the section created at the terminal;

        (c) calculating a blurred estimate of the signal received at the terminal from the
        first transmitter using a first function dependent on the first section and the
        section created at the terminal in step (a);

15   (d) creating a blurred terminal section using a second function dependent on
        the first section and the section created at the terminal in step (a);

        (e) subtracting the blurred estimate from the blurred terminal section to
        produce a blurred residual representation; and

        (f) estimating the time offset between the blurred residual representation and
20   the second section.

2.   A method according to claim 1, wherein the first function, which is used to
create the blurred estimate, is a convolution of the first section of a representation of
the signal transmitted by a first of said transmitters (the 'first section') with a cross-
25   correlation of the section of a representation of the signals from the transmitters
received by the receiver (the 'terminal section') and the first section.

3.   A method according to claim 2, wherein the cross-correlation is a windowed
cross-correlation created by enhancing the significant components of the cross-
30   correlation function.

4.   A method according to any of claims 1 to 3, wherein the second function,
which is used to create the blurred terminal section, is a convolution of the terminal
section with the auto-correlation profile of the first section.

35

5.   A method according to any of claims 1 to 4, wherein the blurred residual
representation is cross-correlated with the second section of a representation of the

REPLACED BY
                ART 34 AMDT

signal transmitted by a second of said transmitters (the 'second section') to estimate the time offset.

6.   A method according to any of claims 1 to 5, wherein the first and second
5   sections are created at the respective first and second transmitters.

7.   A method according to any of claims 1 to 5, wherein the first and second sections are created in one or more sampling devices attached to the respective transmitters or located elsewhere.

10

8.   A method according to any of claims 1 to 5, wherein the first and second sections are created by computer programs running anywhere in the communications network, or elsewhere, using information supplied from the network about the transmitted signals.

15

9.   A method of finding the time offset relative to a reference within the terminal of a component of a signal transmitted by one of a plurality of transmitters of a communications network and received by a receiver attached to a terminal, the method comprising the steps of

20   (a) creating at the terminal a section of a representation of the signals from the transmitters received by the receiver (a "terminal section");
            (b) creating a section of a representation of the signal transmitted by an other transmitter (a "transmitter section"), which section overlaps in time with the section created at the terminal;

25   (c) calculating a blurred estimate of the signal received at the terminal from the other transmitter using a first function dependent on the transmitter section and the terminal section;
            (d) creating a blurred terminal section using a second function dependent on the transmitter section and the terminal section;

30   (e) subtracting the blurred estimate from the blurred terminal section to produce a blurred residual representation; and
            (f) estimating the time offset between the blurred residual representation and the signal component.

35   10.   A method according to claim 9, wherein the first function, which is used to create the blurred estimate, is a convolution of the transmitter section with a cross-correlation of the terminal section and the transmitter section.

23

11. A method according to claim 10, wherein the cross-correlation is a windowed cross-correlation created by enhancing the significant components of the cross-correlation function.

5

12. A method according to any of claims 9 to 11, wherein the second function, which is used to create the blurred terminal section, is a convolution of the terminal section with the auto-correlation profile of the transmitter section.

10 13. A method according to any of claims 9 to 12, wherein the known components of the transmitted signals in the second aspect of the invention are pilot codes.

14. A method according to any of claims 9 to 13, wherein, before the time offset is estimated, the known signal components are blurred by convolution with another

15 function.

15. A method according to any of claims 9 to 14, wherein the section of the representation of the signals transmitted by a transmitter is created at that transmitter.

20 16. A method according to any of claims 9 to 14, wherein the section of the representation of the signals transmitted by a transmitter is created in one or more sampling devices attached to the respective transmitters or located elsewhere.

17. A method according to any of claims 9 to 14, wherein the section of the

25 representation of the signals transmitted by a transmitter is created by a computer program running anywhere in the communications network, or elsewhere, using information supplied from the network about the transmitted signals.

18. A method according to any of claims 1 to 14, wherein the section of the

30 representation of the signals received by the receiver at the terminal is recorded in the terminal before being sent to a computing device.

19. A method according to any of claims 1 to 14, wherein the section of the representation of the signals received by the receiver at the terminal is transferred in

35 real time to the computing device and a recording made there.

24

20.   A method according to any of claims 1 to 19, wherein the representation of the signals received by the receiver attached to the terminal may be a digitised version of the received signals converted first to baseband in the receiver.

5   21.   A method according to any of claims 1 to 20, wherein the representation of the signals transmitted by a transmitter may be a digitised version of the transmitted signals converted first to baseband.

22.   Apparatus including a processing means arranged to carry out the method of
10   any of claims 1 to 21.

23.   Apparatus for finding the time offset between signals transmitted by at least one of a plurality of transmitters of a communications network and received by a receiver attached to a terminal, the apparatus comprising

15   (a) processing means arranged to create at the terminal a section of a representation of the signals from the transmitters received by the receiver;

           (b) processing means arranged to create a first section of a representation of the signal transmitted by a first of said transmitters, and to create a second section of a representation of the signal transmitted by a second of said transmitters, each of

20   which sections overlaps in time with the section created at the terminal;

           (c) processing means arranged to calculate a blurred estimate of the signal received at the terminal from the first transmitter using a first function dependent on the first section and the section created at the terminal in (a) above;

           (d) processing means arranged to create a blurred terminal section using a

25   second function dependent on the first section and the section created at the terminal in (a) above;

           (e) processing means arranged to subtract the blurred estimate from the blurred terminal section to produce a blurred residual representation; and

           (f) processing means arranged to estimate the time offset between the blurred

30   residual representation and the second section.

24.   Apparatus for finding the time offset relative to a reference within the terminal of a component of a signal transmitted by one of a plurality of transmitters of a communications network and received by a receiver attached to a terminal, the

35   apparatus comprising

(a) processing means arranged to create at the terminal a section of a representation of the signals from the transmitters received by the receiver (a "terminal section");

(b) processing means arranged to create a section of a representation of the

5   signal transmitted by an other transmitter (a "transmitter section");

(c) processing means arranged to calculate a blurred estimate of the signal received at the terminal from the other transmitter using a first function dependent on the transmitter section and the terminal section;

(d) processing means arranged to create a blurred terminal section using a

10   second function dependent on the transmitter section and the terminal section;

(e) processing means arranged to subtract the blurred estimate from the blurred terminal section to produce a blurred residual representation; and

(f) processing means arranged to estimate the time offset between the blurred residual representation and the signal component.

15

25.   A telecommunications terminal including apparatus for finding the time offset between signals transmitted by at least one of a plurality of transmitters of a communications network and received by a receiver attached to a terminal, the apparatus comprising

20   (a) processing means arranged to create at the terminal a section of a representation of the signals from the transmitters received by the receiver;

(b) processing means arranged to calculate a blurred estimate of the signal received at the terminal from the first transmitter using a first function dependent on the section created at the terminal in (a) above and a first section of a representation of the signal transmitted by a first of said transmitters which overlaps in time with the

25   section created at the terminal and which is sent to the terminal;

(c) processing means arranged to create a blurred terminal section using a second function dependent on the first section and the section created at the terminal in (a) above;

30   (d) processing means arranged to subtract the blurred estimate from the blurred terminal section to produce a blurred residual representation; and

(e) processing means arranged to estimate the time offset between the blurred residual representation and a second section of a representation of the signal transmitted by a second of said transmitters which overlaps in time with the section

35   created at the terminal and which is sent to the terminal.

26.   A telecommunications terminal including apparatus for finding the time offset relative to a reference within the terminal of a component of a signal transmitted by one of a plurality of transmitters of a communications network and received by a receiver attached to a terminal, the apparatus comprising

5   (a) processing means arranged to create at the terminal a section of a representation of the signals from the transmitters received by the receiver (a "terminal section");

            (b) processing means arranged to calculate a blurred estimate of the signal received at the terminal from an other transmitter using a first function dependent on

10   the terminal section and a section of a representation of the signal transmitted by the other transmitter (a "transmitter section") which is sent to the terminal;

            (c) processing means arranged to create a blurred terminal section using a second function dependent on the transmitter section and the terminal section; ·

            (d) processing means arranged to subtract the blurred estimate from the

15   blurred terminal section to produce a blurred residual representation; and

            (e) processing means arranged to estimate the time offset between the blurred · residual representation and the signal component.

27.   A communications network for finding the time offset between signals

20   transmitted by at least one of a plurality of transmitters of a communications network and received by a receiver attached to a terminal, the network comprising

            (d) a computing device or devices;

            (e) a terminal having a radio receiver attached to the terminal, means for creating a section of a representation of the signals, received by the radio receiver,

25   from the transmitters of the communications network, and means for sending the section to the computing device or devices;

            (f) sampling devices associated with respective first and second of said transmitters for creating respective first and second sections of representations of the signal transmitted by the respective transmitter which

30   overlap in time with the section created at the terminal, and for sending the sections of the representations created at said transmitters to said computing device or devices;

        the computing device or devices being adapted to perform

            1   a calculation of a blurred estimate of the signal received at the terminal

35   from   the first transmitter using a first function dependent on the   first section and the section created at the terminal;

2   a calculation of a blurred terminal section using a second function dependent on the first section and the section created at the terminal;

3   a subtraction of said blurred estimate from the blurred terminal section to produce a blurred residual representation;

5   4   a calculation of the time offset between the blurred residual representation and said second section.

28.   A communications network for finding the time offset relative to a reference within the terminal of a component of a signal transmitted by one of a plurality of

10   transmitters of a communications network and received by a receiver attached to a terminal, the network comprising

(d) a computing device or devices;

(e) a terminal having a radio receiver attached to the terminal, means for creating a section of a representation of the signals, received by the radio receiver,

15   from the transmitters of the communications network (a "terminal section"), and means for sending the section to the computing device or devices;

(f) a sampling device associated with an other transmitter for creating a section of a representation of the signal transmitted by the other transmitter (a "transmitter section") which overlaps in time with the section created at the

20   terminal, and for sending the section of the representations created at the other transmitter to said computing device or devices;

the computing device or devices being adapted to perform

1   a calculation of a blurred estimate of the signal received at the terminal from the other transmitter using a first function dependent on the

25   transmitter section and the terminal section;

2   a calculation of a blurred terminal section using a second function dependent on the transmitter section and the terminal section;

3   a subtraction of said blurred estimate from the blurred terminal section to produce a blurred residual representation;

30   4   a calculation of the time offset between the blurred residual representation and the signal component.

29.   A computing device or devices for use in a communications network comprising a terminal having a radio receiver attached to the terminal, means for

35   creating a section of a representation of the signals, received by the radio receiver, from the transmitters of the communications network, and means for sending the section to the computing device or devices; and sampling devices associated with

28

respective first and second of said transmitters for creating respective first and second sections of representations of the signal transmitted by the respective transmitter which overlap in time with the section created at the terminal, and for sending the sections of the representations created at said transmitters to said

5   computing device or devices,

the computing device or devices being adapted to perform

1 a calculation of a blurred estimate of the signal received at the terminal from the first transmitter using a first function dependent on the first section and the section created at the terminal;

10   2 a calculation of a blurred terminal section using a second function dependent on the first section and the section created at the terminal;

3 a subtraction of said blurred estimate from the blurred terminal section to produce a blurred residual representation;

4 a calculation of the time offset between the blurred residual representation

15   and said second section.

30.   A computing device or devices for use in a communications network comprising a terminal having a radio receiver attached to the terminal, means for creating a section of a representation of the signals, received by the radio receiver,

20   from the transmitters of the communications network (a "terminal section"), and means for sending the section to the computing device or devices; and a sampling device associated with an other transmitter for creating a section of a representation of the signal transmitted by the other transmitter (a "transmitter section") which overlaps in time with the section created at the terminal, and for sending the section

25   of the representations created at the other transmitter to said computing device or devices,

the computing device or devices being adapted to perform

1 a calculation of a blurred estimate of the signal received at the terminal from the other transmitter using a first function dependent on the

30   transmitter section and the terminal section;

2 a calculation of a blurred terminal section using a second function dependent on the transmitter section and the terminal section;

3 a subtraction of said blurred estimate from the blurred terminal section to produce a blurred residual representation;

35   4 a calculation of the time offset between the blurred residual representation and the signal component.

31.   A computer program or programs comprising computer program code means adapted to perform the steps of the computing device of claim 29.

32.   A computer program or programs comprising computer program code means
5   adapted to perform the steps of the computing device of claim 30.

33.   A method of calculating the position of a mobile terminal in a communications network which includes the method of any of claims 1 to 21.